

PLAYGUARD[®]

SAFETY SURFACING

ecore

715 FOUNTAIN AVENUE
LANCASTER, PA 17601
TOLL FREE: 1-800-851-4746
PHONE: (717)295-3400
FAX: (717)295-3414
www.playguardsurfacing.com

NOTE:
FILLER TO PENETRATE
INTO OPENING 1/2" MIN.
FILLER TO EXTEND ABOVE
TILE LINE BY 1/8" AND BE
STRUCK OFF IN A UNIFORM FASHION.

BACKFILL ALL CUTOUTS AROUND
PLAY STRUCTURE SUPPORTS AND
OTHER PENETRATIONS WITH
FILLER COMPOUND

2 1/2" PLAYGUARD TILE, CUT
TILES ALONG PERIPHERY AND
PENETRATIONS AS REQUIRED

RECESS FOR TILE TO BE NO MORE
THAN OVERALL TILE HEIGHT, AND
NO LESS THAN 1/4" BELOW
OVERALL TILE HEIGHT

CUT PLAYGAURD AROUND PENETRATIONS
TO WITHIN 1/4" MAX.
OF PLAY STRUCTURE SUPPORT

EGRIP III ADHESIVE LAYER
APPLIED AT 50-60 SQ FT/GAL.
USE 1/8" SQ. NOTCHED TROWEL

NEW OR EXISTING CONCRETE OR
ASPHALT SURFACE (SEE ECORE
SPECS FOR RECOMMENDATIONS)

COMPACTED EARTH AND
AGGREGATE SUB BASE

CONCRETE FOOTER FOR
STRUCTURE SUPPORT POST

NOTE:
SUBSTRATE MUST BE WELL CURED
(28 DAYS MIN.) AND DRY BEFORE
APPLICATION OF VERSASEAL ADHESIVE

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWINGS.
3. COLOUR TO BE CONFIRMED WITH OWNER PRIOR TO INSTALLATION.

